

*Luxriot Mini NVR/DVR Series are optimized and designed to work with Luxriot VMS for sensitive data storage of IP/Megapixel Cameras and Analog Cameras.*

*Designed for use with Luxriot VMS*



Mini IP NVR Server

## **LUXRIOT MINI NVR/DVR SERVER**

### **Features:**

- Hybrid IP & Analog
- Advanced Intel® Core™ i3-4130, i5-4590S & i7-4790S
- Internal HDD configurations 1TB, 2TB, 3TB & 4TB
- Motherboard Video Adapter with HDMI & DVI outputs
- 8GB of DDR3 Kingston RAM
- Server is pre-installed with Windows® 7 OS on dedicated solid state drive\*
- Advanced form factor ensures extremely quiet operation
- Built-in DVD-RW for high speed archiving

Optimized & Designed for:



## Luxriot Models



Luxriot Mini NVR Models		
LUXR-MINI-SVR-1TB-i3	LUXR-MINI-SVR-4TB-SSDi3*	LUXR-MINI-SVR-4TB-SSDi5*
LUXR-MINI-SVR-2TB-i3	LUXR-MINI-SVR-2TB-SSDi5*	LUXR-MINI-SVR-3TB-SSDi7*
LUXR-MINI-SVR-3TB-SSDi3*	LUXR-MINI-SVR-3TB-SSDi5*	LUXR-MINI-SVR-4TB-SSDi7*

\* Includes 120GB SSD for OS - Can add optional PCI-X Network Card to any Mini Server

## ● Specifications

Luxriot NVR Model	LUXR-MINI-SVR-1TB-i3	LUXR-MINI-SVR-2TB-i3	LUXR-MINI-SVR-3TB-SSDi3	LUXR-MINI-SVR-4TB-SSDi3	LUXR-MINI-SVR-2TB-SSDi5	LUXR-MINI-SVR-3TB-SSDi5	LUXR-MINI-SVR-4TB-SSDi5	LUXR-MINI-SVR-3TB-SSDi7	LUXR-MINI-SVR-4TB-SSDi7
<b>Power Supply</b>	(1) 300W Mini PSU (110~220V Selectable)								
<b>Form Factor</b>	Asus Main board								
<b>Cooling System</b>	1 x 80mm Fan								
<b>Operating System</b>	Windows 7 (64 Bit) on 40GB Partitioned 1TB HD	Windows 7 (64 Bit) on 40GB Partitioned 2TB HD	Windows 7 (64 Bit) on 120GB Intel SSD						
<b>NIC</b>	(1) Internal Gbit Ethernet 1000 Mbps LAN								
<b>DVD/CD RW</b>	Front Panel Access								
<b>Storage</b>	1TB	2TB	3TB	4TB	2TB	3TB	4TB	3TB	4TB
<b>Chassis</b>	Mini ATX Desktop								
<b>Graphics Card</b>	Integrated graphics support for processors with Intel® Graphics Technology (HDMI/DVI/VGA)								
<b>CPU</b>	i3-4130	i3-4130	i3-4130	i3-4130	i5-4590s	i5-4590s	i5-4590s	i7-4790s	i7-4790s
<b>RAM</b>	8 GB fully buffered								
<b>Dimensions (W x D x H)</b>	3.9" x 13.3" x 10.2"								

## ● Optional Capture Boards

Capture Boards	
<b>HC7008L</b>	FULL HEIGHT. 240FPS H.264 D1 at 30FPS/channel board PCI-X1 64Bit Driver- 8 channels Video - 8 channels Audio - 1 video out - 1 Audio out - On board motion detection - NTSC/PAL
<b>HC7016XL</b>	FULL HEIGHT. 480FPS H.264 D1 at 30FPS/channel board PCI-X1 64Bit Driver- 16 channels Video - 16 channels Audio - 2 video out - 2 Audio out - On board motion detection - NTSC/PAL