



Network Video Recorder ND8401



VAST Inside • HD Local Display •
Full Integration with VIVOTEK Network Cameras

VIVOTEK ND8401 is a 16-CH Network Video Recorder designed for sophisticated recording applications. The unit is equipped with an Intel® Dual-core Processor with maximum recording throughput at a robust 96 Mbps. RAID 0/1/5/10 is supported with four HDDs, with an external eSATA port for additional expansion. Like VIVOTEK NVR ND8301, a local display output port is available with Full HD resolution (1920x1080), eliminating the need for a separate PC to view video from the unit. Setup of parameters such as IP address, HDD to logical volumes, and basic camera configuration can easily be performed with the setup wizard, making the ND8401 the easiest NVR to use yet. When connecting ND8401 to more than one of the same model of VIVOTEK camera, the "Shepherd" program can be used to duplicate the configuration to multiple cameras.

VIVOTEK's professional software VAST is installed in ND8401 with performance tuning, allowing for simple and effective management of a surveillance system using the LiveClient and Playback programs. As VIVOTEK's camera features are fully integrated into VAST, cutting-edge technologies such as Activity Adaptive Recording can be utilized to conserve bandwidth and optimize recording. A CMS server running VAST software can also directly control the ND8401, and compatibility with the iViewer application allows for remote access to the ND8401 on handheld devices. By integrating all of the components together using VIVOTEK's ND8401, network cameras, VAST and iViewer software, users can realize a fully-featured and robust next-generation surveillance system.

Features

Hardware

- Windows 7 Embedded
- Dual-Core Intel® Processor
- Standalone Desktop NVR Design
- Full HD Local Display
- RAID 0, 1, 5, 10 Storage Solution
- 4 x HDD Tray, Max. 12TB
- 2 x Gigabit RJ45 Ethernet Port
- 6 x USB Port
- External eSATA Interface
- Size: 204 mm (W) x 330 mm (D) x 215 mm (H)

Software

- Easy Installation and Configuration (Shepherd/Setup Wizard)
- VAST Inside (LiveClient/Playback)
- 16-CH Live View & 1-CH Playback
- H.264, MPEG-4 and MJPEG
- Multiple Recording Types & Event Trigger Sources
- Multiple Video Search Modes
- E-map
- Supported by VAST Central Management Software
- Full Integration with VIVOTEK Network Cameras
- VIVOTEK iViewer Support (iOS/Android)

*The VIVOTEK VAST Central Management Software is not included in the package.




Technical Specifications


| | |
|--|---|
| System CPU: Dual-core Intel® processor RAM: 4GB DDRIII OS: Windows 7 embedded | Local Playback Display layout: 1X1 Playback mode: play, pause, stop, next/frame, next/previous, speed control Search mode: browsing, time, event, bookmark Graphical timeline Snapshot Bookmark design PIP video control Video enhancement Log viewer |
| Channels 16-CH selectable | Remote Liveview Display layout: 1X1, 2X2, 3X3, 4X4, 1+5, 1+12 Snapshot Pan/Tilt/Zoom control of VIVOTEK cameras Simple camera and recording settings |
| Storage 4 x 3.5" HDD, up to 12TB 4 x hot-swappable & lockable hard disk tray HDD S.M.A.R.T. (Self-Monitoring Analysis and Reporting Technology) RAID 0, 1, 5, 10 External eSATA storage | Remote Playback Display layout: 1X1 Playback mode: play, pause, stop, speed control Search mode: browsing, event Graphical timeline |
| Connectors 1 x VGA for Full HD local display 2 x Gigabit RJ45 Ethernet port 6 x USB 2.0 port 1 x RS232 1 x eSATA 1 x MIC in and line in 1 x line out | Event/Action Management Trigger source: motion, temperature, tampering, DI/O, IR, PIR, IVA, video lost, recording error, recording status, substation connection status, storage connection status, storage capacity status, license status, network status & memory status Actions: email, start recording, move to the preset position, set DO, GSM short message & send CGI command |
| Camera Compatibility Full integration with VIVOTEK network cameras Integration with ONVIF network cameras (by project) | Security 5 levels of user roles Multi-level user access with password protection Device buzzer notification (HDD/network) |
| Easy Setup Setup Wizard for network/HDD/camera easy setup IW2 for search internal camera Shepherd for duplicating the camera's configuration to multiple cameras | Backup Manual/scheduled backup |
| Networking IPv4, TCP/IP, HTTP, RTSP/RTMP/RTCP, IGMP, SMTP, DHCP, NTP, DNS, DDNS | Mobile APP Support VIVOTEK iViewer (iOS/Android) |
| Recording Throughput: max. 96 Mbps Recording policy: scheduled (event/continuous modes) and manual recording Video compression: H.264/MJPEG/MPEG-4 Audio compression: AMR/G.711/AAC Resolution: Up to 5-Megapixel recording Format: 3GP Auto recycling: buffer size setting, time setting Activity adaptive recording | Dimension 204 mm (W) x 330 mm (D) x 215 mm (H) |
| Export Format: AVI/3GPP/EXE | Weight Net: 5.24 kg (without HDD) |
| Local LiveClient Display layout: 1X1, 2X2, 3X3, 4X4, 1+5, 1+12 Rotate Snapshot Two way audio control PIP video control Stream selectable Set DO control Video enhancement Pan/Tilt/Zoom control of VIVOTEK cameras Preset location Auto pan/patrol Event popup windows Instant event notification Display performance: MJPEG: 16-CH, 30 fps @ CIF MPEG4: 16-CH, 30 fps @ CIF or 2-CH, 30 fps @ 1080P H.264: 7-CH, 30 fps @ CIF or 1-CH, 30 fps @ 1080P Auto stream size | LED Indicator 1 x Power status 1 x HDD status |
| | Power Input: AC 100-240 V, 50-60 Hz Power consumption: max. 58 W |
| | Approvals CE, FCC Class B, VCCI, C-Tick |
| | Operating Environments Temperature: 0°C ~ 40°C Humidity: 20%~95% RH |
| | Warranty 24 months |
| | Language English, French, German, Italian, Spanish, Traditional Chinese, Simplified Chinese, Japanese, Portuguese, Czech |
| | Included Accessories CD content: user's manual, quick installation guide, installation wizard 2, LiveClient (remote), Playback (remote) Others: quick installation guide, warranty card, power cord |

Application

Multi-site Chain Stores



Dimensions



Part No.

| | | | |
|-------------|------------|----------------|------------|
| ND8401, USA | 100091100G | ND8401, UKB | 100091130G |
| ND8401, AUN | 100091110G | ND8401, Mexico | 100091200G |
| ND8401, EU | 100091120G | | |

All specifications are subject to change without notice. Copyright © 2013 VIVOTEK INC. All rights reserved.

Distributed by:



VIVOTEK INC.

6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C.
 |T: +886-2-82455282 | F: +886-2-8245532 | E: sales@vivotek.com

VIVOTEK USA, INC.

2050 Ringwood Avenue, San Jose, CA 95131
 |T: 408-773-8886 | F: 408-773-8298 | E: salesusa@vivotek.com

Ver 1.0