



BRAVO SR300 ALK

Wireless Outdoor Siren

EN 50131

GRADE 2 Class II

Description

BRAVO SR300 ALK is a wireless piezo siren for outdoor mounting designed for operation in BRAVO wireless intruder alarm systems or with ECLIPSE WL wireless expander module in ECLIPSE hybrid systems. The siren can be located in a distance up to 400m away from the control panel.

BRAVO SR300 ALK is equipped with sound and LED indication for announcing of alarm events, inner metal casing and bidirectional tamper for higher protection. An external adapter 12VDC/1A may be used to power the siren and prolong the battery life. The siren has a flat plastic cover, which is especially suitable for company sticker or logo. BRAVO SR300 ALK wireless siren is certified to EN50131, GRADE 2, Class II.

Technical Specifications

Battery	4x1.5V, alkaline
Battery life	3 years*
Battery low voltage signal	signal sent at value < 5.1VDC
Operation frequency	868MHz
Radio distance (open space)	up to 400m
Loudspeaker type	piezo
Protection of the housing	IP44/IK04
Protection of the electronics	IP55
Programmable alarm cycle	1-3 minutes
Housing	ABS plastic box with inner metal cover
Operation temperature	-10°C ÷ +40°C
Sound volume	110dB/1m
Dimensions	310 x 230 x 60 mm
Weight	~1.240kg



* **Based on normal use of the siren** (e.g. 1 alarm per month with strobe and 1 minute alarm cycle, and 8 squawks per day at an average of 25°C). If the use is more frequent or the alarm cycle is set for more than 1 minute the battery life may be reduced. Using optional power supply with adapter 12V/1A will extend the battery life.

Functional Specifications

- Suitable for outdoor mounting
- Bi-directional tamper switch for self-protection of the box
- Separate alarm notifications for intrusion and fire
- Squawk functionality
- Reset button for restoring the factory settings
- Internal metal cover for increased protection
- Plastic cover for protection of the electronic components
- Additional external power supply with adapter
- Chasing LEDs optional switching

Contact Information



BRAVO SR300 ALK

Wireless Outdoor Siren

EN 50131
GRADE 2 Class II

● Packing Information

- **Single packing box** - 1 unit BRAVO SR300 ALK, dimensions 332 x 238 x 67mm
- **Master packing box** - 5 units BRAVO SR300 ALK, dimensions 360 x 345 x 252mm

● Compatible Product Range

- **BRAVO EXT** - Wireless panel with external power supply
- **BRAVO INTR** - Wireless panel with built-in power supply
- **ECLIPSE WL** - Wireless expander module for ECLIPSE control panels

● Contact Information