

Luxriot DAS - (Direct Attached Storage) units are designed to work with Luxriot VMS servers for sensitive data storage of IP/Megapixel Cameras, HD SDI Cameras and Analog Cameras.

Designed for use with Luxriot VMS



Storage Expansion DAS

LUXRIOT EXTERNAL DAS

Features:

- Hot Swap Storage Bays
- Redundant Power Supply Units
- Daisy Chain Multiple Units (Up To 4 per Raid Controller)
- 3U & 4U Chassis
- Hot Swap Rear Fans

Optimized & Designed for:



A&H Software House Inc.

• Luxriot DAS Models



External 3U 16 Bay DAS 12-39TB (Direct Attached Storage) Raid 6		External 4U 24 Bay DAS 42-84TB (Direct Attached Storage) Raid 6	
LR-DAS-12TBR6+H		LR-DAS-42TBR6+H	LR-DAS-72TBR6+H
LR-DAS-18TBR6+H		LR-DAS-48TBR6+H	LR-DAS-76TBR6+H
LR-DAS-24TBR6+H		LR-DAS-54TBR6+H	LR-DAS-80TBR6+H
LR-DAS-30TBR6+H		LR-DAS-60TBR6+H	LR-DAS-84TBR6+H
LR-DAS-36TBR6+H		LR-DAS-63TBR6+H	
LR-DAS-39TBR6+H		LR-DAS-68TBR6+H	

• Specifications

Luxriot DAS Model	Luxriot 3U DAS Expansion Raid 6	Luxriot 4U DAS Expansion Raid 6
Power Supply	(2) 820W PS (Redundant) (110~240V auto-detect)	(2) 960W PS (Redundant) (110~240V auto-detect)
Form Factor	3U (12TB, 18TB, 24TB, 30TB, 36TB & 39TB)	4U (42TB, 48TB, 54TB, 60TB, 63TB, 68TB, 72TB, 76TB, 80TB & 84TB)
Cooling System	Built-in 4x 80mm Hot Swap PWM Middle Fans	Built-in 4x 80mm Hot Swap PWM Middle Fans
Storage	Hot Swap 12TB-39TB Internal (SATA-6Gb/s/7200 RPM)	Hot Swap 42TB-84TB Internal (SATA-6Gb/s/7200 RPM)
Chassis / Backplane	16 Bay SATA / (1) 6Gb/s mini SAS Port	24 Bay SATA / (1) 6Gb/s mini SAS Port
Dimensions (W x D x H)	17" x 26" x 5.2"	17.1" x 27.5" x 7"

- DAS 16 Bay Storage Unit Detailed



- DAS 24 Bay Storage Unit Detailed

