# **EDN2560**

5 Megapixel IR & WDR Mini Dome Network Camera





## Onvie


















#### **Features**

- 1/3" color CMOS image sensor delivers 5 megapixel resolution
- Mini palm-sized, easy installation
- Provides true day / night functionality with automatic IR filter operation
- Wide dynamic range function
- Extended IR range of up to 10 meters with 19 IR LEDs
- Multi-streaming from H.264, M-JPEG or MPEG-4
- H.264 Up to 10 fps at 2560 x 1920 of video resolution, 30ftps at all the others resolution
- Built-in microphone
- Built-in micro SD card slot enable edge recording
- Support motion detection & email notification
- Power over Ethernet
- Supports live monitoring of video from mobile devices via MobileFocus / MobileFocus Plus Apps (iOS and Android)

### **Specifications**

Image Sensor   1/3" color CMOS   1/4" color CM	Camera		
Image Sensor		EMD	
Lens       4mm, F2.0         Minimum Illumination       0.5 Lux @ F2.0         Day / Night       True Day / Night         Iris       Fixed IRIS         Shutter Time       Auto (1/30 ~ 1/60,000)         Camera Angle Adjustment       Pan: -100°~100°, Tilt: 20°~90° Manual         Video       Video Compression         Max. Video Resolution       2560 x 1920         Frame Rate       10fps @ 2560 x 1920         30fps @ all other res.       5/50dB         AGC       Yes         AWB       Yes         WDR       Yes         Audio Compression       G.711         Operation Mode       1-way audio, Built-in Microphone         Network       Interface       10BASE-T / 100BASE-TX         Supported Protocols       TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP         Security       Password protection, User privilege         Function       Wultiple simultaneous streams         Video Streaming       Multiple simultaneous streams         Image Settings       Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Filip, Auto white balance, Auto exposure control         Event Trigger       Motion detection         Notification       Send mail notification         G			
Minimum Illumination Day / Night True Day / Night Trise Day / Night Trise Day / Night Trise Day / Night Trise Trive IRIS Shutter Time Auto (1/30 ~ 1/60,000) Camera Angle Adjustment Video Video Compression Max. Video Resolution Pan: -100°~100°, Tilt: 20°~90° Manual Video Video Compression Max. Video Resolution Pan: -100° and panual Video Video Compression Max. Video Resolution Pan: -100° and panual Video Video Compression Max. Video Resolution Pan: -100° and panual Video Video Compression Operation Panual Video Video Stode Audio Audio Audio Compression G.711 Operation Mode Panual Video Streaming Tribum Video Streaming Video Streaming Video Streaming Video Streaming Multiple simultaneous streams Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Filp, Auto white balance, Auto exposure control Event Trigger Notification Send mail notification General On-board Storage IR LED (Units) IR Distance Dower Over Ethernet Max. Power Consumption Dic Jack, RJ-45 Operating Temperature O°C-~40°C / 32°F~104°F Dimensions (Φ x H) Video Stream Video Stream Video Streaming O°C-40°C / 32°F~104°F Dimensions (Φ x H) Video Streaming Video St		,	
Day / Night Iris Fixed IRIS Shutter Time Auto (1/30 ~ 1/60,000) Camera Angle Adjustment Video Video Compression Max. Video Resolution Frame Rate S/N Ratio Agc Agc Agc Agc Agc Agc Audio Audio Compression Audio Compression Audio Compression Audio Compression Agc Audio Audio Compression Audio Compress		,	
Iris Fixed IRIS Shutter Time Auto (1/30 ~ 1/60,000) Camera Angle Adjustment Pan: -100°~100°, Tilt: 20°~90° Manual Video Video Compression H.264 / M-JPEG Max. Video Resolution 2560 x 1920 Frame Rate 30fps @ 180 other res. S/N Ratio >50dB AGC Yes AWB Yes WDR Yes Audio Audio Compression G.711 Operation Mode Built-in Microphone Network Interface 10BASE-T / 100BASE-TX Supported Protocols TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP Security Password protection, User privilege Function Video Streaming Multiple simultaneous streams Image Settings Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control Event Trigger Motion detection On-board Storage micro SD / SDHC card slot IR LED (Units) 19 IR Distance 10M / 33ft. Power Supply 12 VDC & PoE Power over Ethernet IEEE 802.3af (Class 3) Max. Power Consumption Occurred Occurred Dack, RJ-45 Operating Temperature O°C~40°C / 32°F~104°F Dimensions (Φ x H) 92 x 63mm / 3.62 x 2.48" Weight 276g / 0.61lbs			
Shutter Time         Auto (1/30 ~ 1/60,000)           Camera Angle Adjustment         Pan: -100°~100°, Tilt: 20°~90° Manual           Video         Wideo Resolution           Max. Video Resolution         2560 x 1920           Frame Rate         10fps @ 2560 x 1920           30fps @ all other res.         S/N Ratio           AGC         Yes           AWB         Yes           WDR         Yes           Audio         Audio Compression           G.711         Operation Mode           Network         1-way audio, Built-in Microphone           Network         1-way audio, Built-in Microphone           Network         1-may audio, Built-in Microphone           Network         1-may audio, Built-in Microphone           Network         1nterface           1nterface         10BASE-T / 100BASE-TX           Supported Protocols         TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPDE, DNS, DHCP, RTSP           Security         Password protection, User privilege           Function         Multiple simultaneous streams           Image Settings         Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control           Event Trigger         Motion detection           Notification <td></td> <td>, , <del>,</del></td>		, , <del>,</del>	
Camera Angle Adjustment       Pan: -100°~100°, Tilt: 20°~90° Manual         Video       H.264 / M-JPEG         Max. Video Resolution       2560 x 1920         Frame Rate       10fps @ 2560 x 1920         30fps @ all other res.       S/N Ratio         AGC       Yes         AWB       Yes         WDR       Yes         Audio       Audio, Person         Audio Compression       G.711         Operation Mode       1-way audio, Built-in Microphone         Network       Interface         Interface       10BASE-T / 100BASE-TX         Supported Protocols       TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP         Security       Password protection, User privilege         Function       Multiple simultaneous streams         Video Streaming       Multiple simultaneous streams         Image Settings       Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control         Event Trigger       Motion detection         Notification       Send mail notification         General       On-board Storage       micro SD / SDHC card slot         IR LED (Units)       19         IR Distance       10M / 33ft.         Power Suppl			
Video       Video Compression       H.264 / M-JPEG         Max. Video Resolution       2560 x 1920         Frame Rate       10fps @ 2560 x 1920         30fps @ all other res.       5/0dB         AGC       Yes         AWB       Yes         WDR       Yes         Audio       Audio Compression         Operation Mode       1-way audio, Built-in Microphone         Network       Interface         Interface       10BASE-T / 100BASE-TX         Supported Protocols       TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP         Security       Password protection, User privilege         Function       Wultiple simultaneous streams         Video Streaming       Multiple simultaneous streams         Image Settings       Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control         Event Trigger       Motion detection         Notification       Send mail notification         General       On-board Storage       micro SD / SDHC card slot         IR LED (Units)       19         IR Distance       10M / 33ft.         Power Supply       12 VDC & PoE         Power over Ethernet       IEEE 802.3af (Class 3)			
Video Compression  Max. Video Resolution  Frame Rate  30fps @ 32560 x 1920  Frame Rate  30fps @ all other res.  S/N Ratio  >50dB  AGC  Yes  AWB  Yes  WDR  Audio Compression  Operation Mode  Network  Interface  10BASE-T / 100BASE-TX  Supported Protocols  Security  Password protection, User privilege  Function  Video Streaming  Multiple simultaneous streams  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Notification  General  On-board Storage  IR LED (Units)  IR Distance  10 Video Streamption  Max. Power Consumption  Connector  DC Jack, R1-45  Operating Temperature  Dimensions (Φ x H)  Weight  276g / 0.61lbs  100BASE-TX  10F120  10F120		Pan: -100°~100°, Tilt: 20°~90° Manual	
Max. Video Resolution  Frame Rate  10fps @ 2560 x 1920 30fps @ all other res.  S/N Ratio  SoddB  AGC  AWB  Yes  WDR  Audio Compression  Operation Mode  Network  Interface  10BASE-T / 100BASE-TX  Supported Protocols  Security  Password protection, User privilege  Function  Video Streaming  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Notification  General  On-board Storage  IR LED (Units)  IR Distance  Power Supply  Power Ornsumption  Connector  Operating Temperature  Dimensions (Φ x H)  Weight  276g / 0.61lbs  Pess  Ves  Audio  AGC  Yes  AUGU  10FR Sp0  10BASE-T  10BASE-T  10BASE-T  10BASE-TX  1			
Frame Rate  10fps @ 2560 x 1920 30fps @ all other res.  S/N Ratio  >50dB  AGC  Yes  WDR  Audio  Audio Compression  Operation Mode  Network  Interface  10BASE-T / 100BASE-TX  Supported Protocols  Security  Password protection, User privilege  Function  Video Streaming  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Notification  Send mail notification  General  On-board Storage  IR LED (Units)  IR Distance  10M / 33ft.  Power Supply  Power over Ethernet  Max. Power Consumption  Connector  DC Jack, RJ-45  Operating Temperature  O°C~40°C / 32°F~104°F  Dimensions (Φ x H)  Weight  276g / 0.61lbs		,	
Frame Rate  \$JOfps @ all other res.  \$JN Ratio  \$50dB  \$AGC  Yes  \$WDR  Audio  Audio  Audio Compression  Qeration Mode  \$Network  Interface  \$10BASE-T / 100BASE-TX  Supported Protocols  \$CONTROLOR PRISE  \$Security  \$Password protection, User privilege  Function  Video Streaming  \$Multiple simultaneous streams  Image Settings  \$Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  \$Vent Trigger  \$Notification  \$Send mail notification  \$General  On-board Storage  \$IR LED (Units)  \$IR Distance  \$Power over Ethernet  \$Max. Power Consumption  Connector  \$DC Jack, RJ-45  Operating Temperature  \$Discontine Sold Bills  \$Ves Add Sold Sold Sold Sold Sold Sold Sold So	Max. Video Resolution		
AGC Yes  AWB Yes  WDR Yes  Audio  Audio Compression  Operation Mode  Network  Interface  Interface	Frame Rate		
AWB WDR Audio Audio Compression Queration Mode Audio Compression Queration Mode Resiltation Microphone  Network Interface Int	S/N Ratio	>50dB	
WDR Audio Audio Compression G.711 Operation Mode Built-in Microphone Network Interface Interface Supported Protocols Security Password protection, User privilege Function Video Streaming Image Settings Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control Event Trigger Notification Send mail notification General On-board Storage IR LED (Units) IR Distance Power Supply Power Over Ethernet Max. Power Consumption Connector Operating Temperature Dimensions (Φ x H) Veight  Password protection, User privilege Multiple simultaneous streams Multiple simultaneous streams Flip, Auto white balance, Auto exposure control Send mail notification Send mail notification General On-board Storage Index SD / SDHC card slot IR LED (Units) In Distance Index York IEEE 802.3af (Class 3) IEEE 802.3af (	AGC	Yes	
Audio Compression  Audio Compression  Operation Mode  Interface  10BASE-T / 100BASE-TX  Supported Protocols  TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP  Security  Password protection, User privilege  Function  Video Streaming  Multiple simultaneous streams  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Motion detection  Notification  Send mail notification  General  On-board Storage  micro SD / SDHC card slot  IR LED (Units)  19  IR Distance  10M / 33ft.  Power Supply  12 VDC & PoE  Power over Ethernet  IEEE 802.3af (Class 3)  Max. Power Consumption  Poe 4.7W(IR LEDs on)	AWB	Yes	
Audio Compression  Operation Mode  Departion Mode  Reway audio, Built-in Microphone  Network  Interface  Interface  Interface  IOBASE-T / 100BASE-TX  Supported Protocols  TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP  Security  Password protection, User privilege  Function  Video Streaming  Multiple simultaneous streams  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Motion detection  Notification  Send mail notification  General  On-board Storage  In LED (Units)  In Distance  In M/ 33ft.  Power Supply  Iz VDC & PoE  Power over Ethernet  Max. Power Consumption  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  Video Streaming  Multiple simultaneous streams  Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Motion detection  Notification  Send mail notification  General  On-board Storage  In Motion detection  Notification  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  General  On-board Storage  In Motion detection  Send mail notification  Send mail notification  General  On-board Storage  Motion detection  Notification  Send mail	WDR	Yes	
Operation Mode  1-way audio, Built-in Microphone  Network  Interface  10BASE-T / 100BASE-TX  Supported Protocols  TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP  Security  Password protection, User privilege  Function  Video Streaming  Multiple simultaneous streams  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Notification  Send mail notification  General  On-board Storage  IR LED (Units)  IR Distance  10M / 33ft.  Power Supply  12 VDC & PoE  Power over Ethernet  Max. Power Consumption  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  92 x 63mm / 3.62 x 2.48"  Weight	Audio		
Departion Mode   Built-in Microphone	Audio Compression	G.711	
Network         Interface         10BASE-T / 100BASE-TX           Supported Protocols         TCP / IP, HTTP, SMTP, FTP, DDNS, UPNP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP           Security         Password protection, User privilege           Function         Multiple simultaneous streams           Image Settings         Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control           Event Trigger         Motion detection           Notification         Send mail notification           General         On-board Storage           IR LED (Units)         19           IR Distance         10M / 33ft.           Power Supply         12 VDC & POE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs	Operation Mode		
Interface 10BASE-T / 100BASE-TX Supported Protocols TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP Security Password protection, User privilege Function Video Streaming Multiple simultaneous streams Image Settings Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control Event Trigger Motion detection Notification Send mail notification General On-board Storage micro SD / SDHC card slot IR LED (Units) 19 IR Distance 10M / 33ft. Power Supply 12 VDC & PoE Power over Ethernet IEEE 802.3af (Class 3) Max. Power Consumption PoE 4.7W(IR LEDs on) PoE 4.7W(IR LEDs on) Connector DC Jack, RJ-45 Operating Temperature 0°C~40°C / 32°F~104°F Dimensions (Φ x H) 92 x 63mm / 3.62 x 2.48" Weight 276g / 0.61bs	Network	Built III I licrophone	
Supported Protocols  TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP, RTSP  Security  Password protection, User privilege  Function  Video Streaming  Multiple simultaneous streams  Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Motion detection  Notification  Send mail notification  General  On-board Storage  micro SD / SDHC card slot  IR LED (Units)  19  IR Distance  10M / 33ft.  Power Supply  12 VDC & PoE  Power over Ethernet  IEEE 802.3af (Class 3)  Max. Power Consumption  PoE 4.7W(IR LEDs on)  PoE 4.7W(IR LEDs on)  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  92 x 63mm / 3.62 x 2.48"  Weight		10RASE-T / 100RASE-TY	
Security Password protection, User privilege Function Video Streaming Multiple simultaneous streams Image Settings Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control Event Trigger Motion detection Notification Send mail notification  General On-board Storage micro SD / SDHC card slot IR LED (Units) 19 IR Distance 10M / 33ft. Power Supply 12 VDC & PoE Power over Ethernet IEEE 802.3af (Class 3) Max. Power Consumption PoE 4.7W(IR LEDs on) PoE 4.7W(IR LEDs on) Connector DC Jack, RJ-45 Operating Temperature 0°C~40°C / 32°F~104°F Dimensions (Φ x H) 92 x 63mm / 3.62 x 2.48" Weight 276g / 0.61lbs		TCP / IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS,	
Function         Video Streaming         Multiple simultaneous streams           Image Settings         Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control           Event Trigger         Motion detection           Notification         Send mail notification           General         On-board Storage           On-board Storage         micro SD / SDHC card slot           IR LED (Units)         19           IR Distance         10M / 33ft.           Power Supply         12 VDC & POE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           PoE 4.7W(IR LEDs on)         POE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs	Security		
Video Streaming     Multiple simultaneous streams       Image Settings     Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control       Event Trigger     Motion detection       Notification     Send mail notification       General     On-board Storage       IR LED (Units)     19       IR Distance     10M / 33ft.       Power Supply     12 VDC & PoE       Power over Ethernet     IEEE 802.3af (Class 3)       Max. Power Consumption     12 VDC 4.6W(IR LEDs on)       Connector     DC Jack, RJ-45       Operating Temperature     0°C~40°C / 32°F~104°F       Dimensions (Φ x H)     92 x 63mm / 3.62 x 2.48"       Weight     276g / 0.61lbs	, , , , , ,		
Image Settings  Contrast, Brightness, Saturation, Sharpness, Mirroring of images, Flip, Auto white balance, Auto exposure control  Event Trigger  Motion detection  Notification  General  On-board Storage  IR LED (Units)  IP  IR Distance  10M / 33ft.  Power Supply  12 VDC & PoE  Power over Ethernet  IEEE 802.3af (Class 3)  12 VDC 4.6W(IR LEDs on)  PoE 4.7W(IR LEDs on)  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  92 x 63mm / 3.62 x 2.48"  Weight		Multiple cimultaneous streams	
Notification         Send mail notification           General         On-board Storage         micro SD / SDHC card slot           IR LED (Units)         19           IR Distance         10M / 33ft.           Power Supply         12 VDC & PoE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           PoE 4.7W(IR LEDs on)         PoE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs		Contrast, Brightness, Saturation, Sharpness, Mirroring of images,	
Notification         Send mail notification           General         Micro SD / SDHC card slot           On-board Storage         micro SD / SDHC card slot           IR LED (Units)         19           IR Distance         10M / 33ft.           Power Supply         12 VDC & PoE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           PoE 4.7W(IR LEDs on)         PoE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs	Event Trigger	Motion detection	
General         On-board Storage         micro SD / SDHC card slot           IR LED (Units)         19           IR Distance         10M / 33ft.           Power Supply         12 VDC & PoE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           PoE 4.7W(IR LEDs on)         PoE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs		Send mail notification	
IR LED (Units)  IR Distance  10M / 33ft.  Power Supply  12 VDC & POE  Power over Ethernet  Max. Power Consumption  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  Weight  19  12 VDC & POE  12 VDC & OE  12 VDC 4.6W(IR LEDs on)  POE 4.7W(IR LEDs on)  POE Jack, RJ-45  Operating Temperature  0°C~40°C / 32°F~104°F  Dimensions (Φ x H)  276g / 0.61lbs	General		
IR LED (Units)  IR Distance  10M / 33ft.  Power Supply  12 VDC & POE  Power over Ethernet  Max. Power Consumption  Connector  DC Jack, RJ-45  Operating Temperature  Dimensions (Φ x H)  Weight  19  12 VDC & POE  12 VDC & OE  12 VDC 4.6W(IR LEDs on)  POE 4.7W(IR LEDs on)  POE Jack, RJ-45  Operating Temperature  0°C~40°C / 32°F~104°F  Dimensions (Φ x H)  276g / 0.61lbs	On-board Storage	micro SD / SDHC card slot	
IR Distance 10M / 33ft.  Power Supply 12 VDC & PoE  Power over Ethernet IEEE 802.3af (Class 3)  Max. Power Consumption 12 VDC 4.6W(IR LEDs on)  PoE 4.7W(IR LEDs on)  Connector DC Jack, RJ-45  Operating Temperature 0°C~40°C / 32°F~104°F  Dimensions (Φ x H) 92 x 63mm / 3.62 x 2.48"  Weight 276g / 0.61lbs		,	
Power Supply         12 VDC & PoE           Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs		10M / 33ft.	
Power over Ethernet         IEEE 802.3af (Class 3)           Max. Power Consumption         12 VDC 4.6W(IR LEDs on) PoE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs		·	
Max. Power Consumption         12 VDC 4.6W(IR LEDs on) PoE 4.7W(IR LEDs on)           Connector         DC Jack, RJ-45           Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs			
Operating Temperature         0°C~40°C / 32°F~104°F           Dimensions (Φ x H)         92 x 63mm / 3.62 x 2.48"           Weight         276g / 0.61lbs		12 VDC 4.6W(IR LEDs on)	
Dimensions (Φ x H)       92 x 63mm / 3.62 x 2.48"         Weight       276g / 0.61lbs	Connector	DC Jack, RJ-45	
Dimensions (Φ x H)       92 x 63mm / 3.62 x 2.48"         Weight       276g / 0.61lbs	Operating Temperature	0°C~40°C / 32°F~104°F	
Weight 276g / 0.61lbs		92 x 63mm / 3.62 x 2.48"	
		•	

#### **Dimensions**



- \* All product specifications are subject to change without notice
- $^{st}$  Models vary in different countries. Please visit EverFocus regional websites for detailed ordering information
- \* Lens models and availbility vary in different regions

