Color Cameras Indoor Box Cameras

EQ610e

700 TVL, True Day/Night, D-WDR **Indoor Box Camera**



OSD















*Lens sold separately

Features

- 700 TVL superior image quality with SONY 1/3" EXview HAD CCD II 960H sensor
- SONY Effio-E platform to provide advanced camera functions
- True Day/Night with ICR module


DNR BLC
ON/OFF

- High sensitivity, low smear, high anti-blooming and high S/N ratio for high performance video
- Easy to use OSD Setup Menu
- D-WDR functions by SONY ATR technology fit backlight conditions
- Built-in Back Light Compensation (BLC), Auto Electronic Shutter (AES), Auto Gain Control (AGC) and Auto White Balance (AWB)
- Built-in Motion Detection, Privacy Mask advanced surveillance functions

Specifications

Pickup Device	1/3" SONY 960H EXview HAD CCD II	
Video Format	NTSC	PAL
Picture Elements	1020(H) x 508(V)	1020(H) x 596(V)
Horizontal Resolution	700 TVL	
Sensitivity	0.03 Lux/F=1.2	
S/N Ratio	Over 52dB (AGC off)	
Video Output	1.0Vp-p Composite, 75Ω; BNC	
Gamma Correction	0.45	
Lens Type	C/CS Mount (Lens sold separately)	
Back Light Compensation	HLC/BLC/OFF	
Auto Electronic Shutter	1/60(50) ~1/100,000sec.	
Auto Gain Control	AUTO (4 Steps)	
Auto White Balance	ATW / Push / User1 / User2 / ANTI CR / Manual / Push Lock	
Sync. Mode	Internal	
OSD Menu	OSD Control (English / Japanese / German / French / Russian / Portuguese / Spanish / Simplified Chinese)	
DNR	On/Off switch	
D-WDR(ATR)	On/Off switch	
Mirror	On/Off switch	
Flicker less	On/Off Switch	
Motion Detection	On/Off for 24x16 Detection Zone Blocks	
Privacy Mask	On/Off for 8 Zones Programmable, Mosaic	
Power Source	Two typs: 90-260VAC~ or 12 VDC/24 VAC~	
Power Consumption	12 VDC/24 VAC~: 2W max. 90-260 VAC~: 3W max.	
Operating Temperature	-10°C~50°C / 14°F~122°F	
Dimensions (W x D x H)	68 x 56 x 120mm/2.6" x 2.2" x 4.7"	
Weight	290g/0.64lbs	
Certificates	CE, FCC	

Dimensions



^{*} Models vary in different countries. Please visit EverFocus regional websites for detailed ordering information

^{*} Lens models and availability vary in different regions