

EXD300e

700 TVL, 3-Axis High Resolution Compact Indoor Dome Camera

NEW



700 TVL	3-Axis	Indoor	Motion Detection Support	Privacy Mask
Vari-Focal DC Iris 2.8~10.5mm	POWER 12VDC/24VAC	BLC ON/OFF	DNR Yes	OSD Yes
AWB Yes	AGC ON/OFF	AES 1/50(1/60)~100,000s	D-WDR ATR	CE

FEDERAL COMMUNICATIONS COMMISSION U.S.A.

Indoor Dome Camera

Features

- 3-Axis camera with SONY 1/3" EXview HAD CCD II 960H sensor, 700 TVL resolution
- SONY Effio-E platform to provide advanced camera functions
- Vari-Focal DC Iris Lens 2.8~10.5mm
- High sensitivity, low smear, high anti-blooming and high S/N ratio for high performance video
- D-WDR functions by SONY ATR technology
- Built-in Auto Electronic Shutter (AES), Auto Gain Control (AGC) and Auto White Balance (AWB)
- Built-in Motion Detection, Privacy Mask advanced surveillance functions

Specifications

Pickup Device	1/3" SONY EXview HAD CCD II (960H)
Video Format	NTSC / PAL (depends on model selected)
Picture Elements	976 x 494 (NTSC), 976 x 582 (PAL)
Horizontal Resolution	700 TVL
Sensitivity	0.03 Lux/F=1.2
S/N Ratio	Over 48dB (AGC off)
Electronic Shutter	1/50 (1/60)~1/100,000sec.
Video Output	BNC 1.0Vp-p, 75Ω
Gamma Correction	0.45
Lens Type	Vari-Focal DC Iris Lens 2.8~10.5mm
Back Light Compensation	On/Off
Auto Gain Control	Yes
White Balance	Auto / Indoor / Outdoor / Manual / Push Auto
Sync. Mode	Internal Sync.
Day & Night	Yes
OSD menu	Yes (English / Japanese / German / French / Russian / Portuguese / Spanish / Simplified Chinese)
DNR	On/Off
D-WDR(ATR)	On/Off
Mirror	On/Off
Motion Detection	On/Off for 24x16 Detection Blocks
Privacy Mask	On/Off for 8 Areas (Size Adjustable)
Power Source	12VDC
Power Consumption	12VDC: 120mA/1.5W max
Humidity	20%~80% non-condensing
Operating Temperature	-10°C~40°C; 14°F~104°F
Dimensions	111.4 x 83mm/4.38" x 3.27"
Weight	440g/0.9lbs
Certificates	CE, FCC

Dimensions

