Color Cameras Outdoor Dome Cameras

ED360

540 TVL, Vari-Focal Vandal Proof & Weather Resistant Color Dome Camera
























Features

- Color dome camera with SONY 1/3" Super HAD CCD sensor
- High resolution 540 TVL
- Employs Digital Signal Processor (DSP) chip-set for image control
- High sensitivity, low smear, high anti-blooming and high S/N ratio
- Built-in Auto Gain Control (AGC), Auto White Balance (AWB)
- Built-in 3.5~8.5mm vari-focal DC-drive Auto Iris lens
- Vandal Proof to withstand impact of a 10 pound sledgehammer
- Weather Resistant IP66 rated

Specifications

Pickup Device	1/3" SONY Super HAD CCD sensor
Video Format	NTSC or PAL (depends on model selected)
Picture Elements	768 x 494 (NTSC), 752 x 582 (PAL)
Horizontal Resolution	540 TVL
Sensitivity	0.12 Lux / F1.6
S/N Ratio	Over 48dB (AGC off)
Electronic Shutter	1/60(1/50)s~1/100,000sec.
Video Output	BNC 1.0Vp-p, 75Ω
Gamma Correction	0.45
Lens Type	Vari-Focal 3.5~8.5mm / F1.6 DC Drive Auto Iris Lens
Gain Control	Automatic
White Balance	AWB (2500°K~9500°K)
Sync. Mode	Internal Sync.
Weather Resistant	IP 66
Vandal Proof	Yes
Power Source	12VDC
Power Consumption	12VDC: 2.4W max.
Operating Temperature	-10°C~50°C / 14°F~122°F
Dimensions (O.D. x H)	142 x 84mm/5.6" x 3.3"
Weight	576g/1.27lbs
Certificates	CE, FCC

Dimensions



^{*} Models vary in different countries. Please visit EverFocus regional websites for detailed ordering information

^{*} Lens models and availability vary in different regions