

FIRE ALARM DETECTORS

INTRUDER ALARM SYSTEMS



SensoMAG F10 INTR

- Fixed temperature fire alarm detector with relay base
- Digital process algorithm
- Detects temperature over 60°C
- LED indication with 360° visibility
- Protected area - up to 35m²
- Low profile design
- Low current consumption



SensoMAG R20 INTR

- Rate-of-rise temperature fire alarm detector with relay base
- Digital process algorithm
- Detects temperature over 58°C or change in temperature for a period of time
- LED indication with 360° visibility
- Protected area - up to 35m²
- Low profile design
- Low current consumption



SensoMAG S30 INTR

- Optical-smoke fire alarm detector with relay base
- Digital process algorithm
- Automatic drift compensation
- LED indication with 360° visibility
- Gasket ring for additional protection to the smoke chamber against dust and dirt
- Protected area - up to 120m²
- Low profile design
- Low current consumption



SensoMAG M40 INTR

- Combined optical-smoke and rate-of-rise fire alarm detector with relay base
- Digital process algorithm
- Automatic drift compensation
- LED indication with 360° visibility
- Gasket ring for additional protection to the smoke chamber against dust and dirt
- Protected area - up to 120m²
- Low profile design
- Low current consumption



Deep Base

- Compatible with SensoMAG series bases
- For mounting on rough surfaces, outdoor pipelines, floating ceilings, etc