

SIRENS

CONVENTIONAL



SF 100

- Indoor fire alarm siren and strobe
- Piezo sounder
- LED strobe
- Sound output: High level - 100dB; Low level - 92dB
- Low profile design
- Max. consumption 20mA@27VDC
- 32 Sound types
- 2 Outputs for evacuation and fire alarm
- Two-wire connection

EN54 - 3



SF 105

- Indoor fire alarm siren
- Piezo sounder
- Sound output - 105dB
- LED strobe
- Plastic case
- Power supply - 24V
- Two-wire connection
- Current - 80mA

EN54 - 3



SF 110

- Indoor fire alarm siren
- Piezo sounder
- Sound output - 100dB
- Power supply - 24V
- Plastic case
- Current - 100mA

EN54 - 3



SF 200

- Outdoor fire alarm siren
- LED strobe
- 1 status indicator
- Sound output - 96dB
- Power supply - 20-30VDC
- Plastic case
- IP54 protection for the electronic part
- Current consumption - <17mA@24V

EN54 - 3



SF 300

- Outdoor fire alarm siren
- LED strobe
- Sound output - 96dB
- Power supply - 20-30VDC
- Plastic case
- IP54 protection for the electronic part
- Current consumption - <17mA@24V

EN54 - 3