# **SENSOIRIS**

# ADDRESSABLE SIRENS/STROBES



# SensolRIS WSOU /IS

• Wall mount sounder

• Sound - Low level: 92dB; High level: 100dB

• 32 sound types selectable from the panel

• Supports Teletek Electronics protocol

• Loop synchronization for better alarm signal

Loop powered

• Color - red

• Available in version with built-in isolator (SensoIRIS WSOU IS)

• IP43C, type B



#### SensolRIS WS /IS

• Wall mount sounder and strobe

• Sound - Low level: 92dB; High level: 100dB

• 32 sound types selectable from the panel

• Supports Teletek Electronics protocol

• Loop synchronization for better alarm signal

Loop powered

• Color - red, transparent

• Available in version with built-in isolator (SensoIRIS WS IS)

• IP43C, type B



# SensolRIS WSST EN54-23 (VAD)/IS

• Wall mount sounder and strobe

• Sound - Low level: 92dB; High level: 100dB

• 32 sound types selectable from the panel

• Supports Teletek Electronics protocol

Loop synchronization for better alarm signal

Loop powered

• Color - white, transparent

• Available in version with built-in isolator (SensoIRIS WSST EN54-23 IS)

• IP43C, type B

• Coverage volume: W-2.4-6



#### SensolRIS BSOU /IS

• Base with built-in sounder, compatible with SensolRIS detector series

• Suitable for wall or ceiling mounting

• Sound - Low level: 92dB; High level: 99dB

• 32 sound types selectable from the panel

• Supports Teletek Electronics protocol

• Loop synchronization for better alarm signal

Loop powered

• Color - white

• Available in version with built-in isolator (SensoIRIS BSOU IS)

• IP21C, type A

• Optional cover when the base is used only as a sounder



### SensolRIS BSST /IS

• Base with built-in sounder and strobe, compatible with SensoIRIS detector series

• Sound - Low level: 92dB; High level: 99dB

• 32 sound types selectable from the panel

• Supports Teletek Electronics protocol

• Loop synchronization for better alarm signal

Loop powered

• Color - white

• Available in version with built-in isolator (SensoIRIS BSST IS)

• IP21C, type A

• Optional cover when the base is used only as a sounder



EN54-3

EN54-3

EN54-3/23 EN54-17

EN54-3

EN54-17



EN54-3