

Cisco Small Business High Power Gigabit Power over Ethernet Injector

Freedom to Install Access Points Anywhere

Highlights

- Provides DC power to the Cisco[®] Small Business WAP371 Wireless-AC/N Dual Radio Access Point when Power over Ethernet cannot be used
- · Guarantee output power up to 30 watts
- · Includes peace-of-mind coverage with limited lifetime hardware warranty

Product Overview

The Cisco Small Business High Power Gigabit Power over Ethernet Injector allows flexible installation of Cisco Small Business Wireless Access Points by providing an alternative to external DC power when deploying a Power over Ethernet (PoE) switch is not an option. Gigabit Ethernet ports provide high-speed connectivity to the LAN. By combining data and power over a single Cat5e or better cable, the injector offer up to 30w output power to power remote devices that required additional power, such as new access points, IP phones and advance IP cameras.

Features

- Delivers PoE connectivity to 802.3at compliant endpoint devices and backward compatible with 802.3af
- · Compatible with Cisco Small Business Wireless Access Points
- · Compact design fits easily in WLAN Access Point installations
- Gigabit LAN ports provide high-speed connectivity to the LAN and endpoint device
- Adds PoE capability to a non-PoE Ethernet switch or router

Benefits

- Easy to use: The Cisco Small Business Gigabit Power over Ethernet Injector is easy to use; simply connect the injector to the PoE endpoint and to an Ethernet switch to provide midspan power.
- Supports wireless LAN deployments: The Cisco Small Business High Power Gigabit Power over Ethernet Injector works with Cisco Small Business Wireless Access Points to provide wireless LAN connectivity for small to medium-sized businesses.
- Enables network expansion: Add PoE capabilities to non-PoE Ethernet switches to provide combined power and data over a single Cat5e or better connection.
- Offers investment protection: Protect the investment of your existing Ethernet equipment and cabling infrastructure by using this high power remote PoE solution.
- **Provides peace of mind:** All Cisco Small Business networking products are protected for the life of the product by the Cisco limited lifetime hardware warranty.

Offers optional Cisco Small Business Support Service: Optional service offers affordable, 3-year peaceof-mind coverage. This subscription-based, device-level service helps you protect your investment and
derive maximum value from Cisco Small Business products. Delivered by Cisco and backed by a trusted
partner, this comprehensive service includes software updates, extended access to the Cisco Small
Business Support Center, and expedited hardware replacement, should it be required.

Specifications

Table 1 lists the specifications, package contents, and minimum requirements for the Cisco Small Power over Ethernet Injector.

 Table 1.
 Specifications for the Cisco Small Business Gigabit Power Over Ethernet Injector-30W

| · | Description | |
|---|--|--|
| Specifications | Description | |
| Standards | IEEE 802.3at, IEEE 802.3af | |
| Ports | Two 10/100/1000 Gigabit Ethernet ports: 1 data uplink, 1 power + data | |
| Cabling type | Category 5e or better | |
| LEDs | Channel Power (green) | |
| Physical Interfaces | | |
| Ethernet ports | Two 10/100/1000 Gigabit Ethernet ports: 1 LAN uplink, 1 PoE port | |
| Input power | AC input voltage: 90-264 VAC AC input current: 0.8A @ 100-240 VAC AC frequency: 50-60 Hz | |
| Output power | Output power voltage: 55 Vdc Output power wattage: 30 Watts (Guarantee) | |
| RJ-45 pin assignment and polarity | Power: Pins 4/5(+), 7/8(-) | |
| Physical Specifications | | |
| Physical dimensions (W x D x | H) 2.09 x 5.5 1.28 in. or 53 x 140 x 32.5 mm | |
| Weight | 0.44 lb or 200 g | |
| Mounting and Physical Securi | ty | |
| Mounting | Surface mountable | |
| Environmental | | |
| Power | IEEE 802.3at (PoE) compliant | |
| Certifications | FCC Class B, CE, UL/cUL, RoHS | |
| Operating temperature | 0° to 40°C (32° to 104°F) | |
| Storage temperature | -20° to 70°C (-4° to 158°F) | |
| Operating humidity | 10% to 85% noncondensing | |
| Storage humidity | 5% to 90% noncondensing | |
| Reliability | MTBF: 100,000 hrs @ 25°C | |
| Thermal Rating | 20 BTU/hr @ 240 VAC | |
| Package Contents | | |
| Cisco Small Business Gigabit Power over Ethernet Injector (30W) Power cord Installation guide Pointer card | | |

| Specifications | Description | |
|---|------------------|--|
| Minimum Requirements | | |
| PoE endpoint device | | |
| Ethernet switch for uplink connectivity | | |
| • 2 Cat5e or better patch cables | | |
| Wiring standards: EIA 568A and 568B | | |
| Warranty | | |
| PoE Injector | Limited Lifetime | |

Ordering Information

| Part Number | Description |
|----------------|--|
| SB-PWR-INJ2-NA | Cisco Small Business Power over Ethernet Injector-30W (North America) |
| SB-PWR-INJ2-AU | Cisco Small Business Power over Ethernet Injector-30W (Australia, New Zealand) |
| SB-PWR-INJ2-AR | Cisco Small Business Power over Ethernet Injector-30W (Argentina) |
| SB-PWR-INJ2-BR | Cisco Small Business Power over Ethernet Injector-30W (Brazil) |
| SB-PWR-INJ2-CN | Cisco Small Business Power over Ethernet Injector-30W (China, Hong Kong) |
| SB-PWR-INJ2-EU | Cisco Small Business Power over Ethernet Injector-30W (Europe) |
| SB-PWR-INJ2-UK | Cisco Small Business Power over Ethernet Injector-30W (United Kingdom) |
| SB-PWR-INJ2-KR | Cisco Small Business Power over Ethernet Injector-30W (Korea) |

Cisco Limited Lifetime Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a limited lifetime warranty for complete peace of mind. Product warranty terms and other information applicable to Cisco products are available at http://www.cisco.com/go/warranty.

For More Information

For more information on Cisco Small Business products and solutions, visit http://www.cisco.com/smallbusiness.



Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-731787-02 04/15