



BRAVO SR300 Li

Wireless Outdoor Siren

EN 50131
GRADE 2 Class IV

Description

BRAVO SR300 Li is a wireless piezo siren for outdoor mounting designed for operation in BRAVO wireless intruder alarm systems or with ECLIPSE WL wireless expander module in ECLIPSE hybrid systems. The siren can be located in a distance up to 400m away from the control panel.

BRAVO SR300 Li is equipped with sound and LED indication for announcing of alarm events, inner metal casing and bidirectional tamper for higher protection. An external adapter 12VDC/1A may be used to power the siren and extend the battery life. The siren has a flat plastic cover, which is especially suitable for company sticker or logo.

BRAVO SR300 Li wireless siren is certified to EN50131, GRADE 2, Class IV.

Technical Specifications

Battery package	Lithium type, 2x3V size "D" or 4x3V size "A"
Battery life	3 years*
Battery low voltage signal	signal sent at value < 5.5VDC
Operation frequency	868MHz
Radio distance (open space)	up to 400m
Loudspeaker type	piezo
Protection of the housing	IP44/IK04
Protection of the electronics	IP55
Programmable alarm cycle	1-3 minutes
Housing	ABS plastic box with inner metal cover
Operation temperature	-25°C ÷ +60°C
Sound volume	110dB/1m
Dimensions	310 x 230 x 60 mm
Weight	~1.240kg



* **Based on normal use of the siren** (e.g. 2 alarms per month with strobe and 1 minute alarm cycle, and 8 squawks per day at an average of 25°C). If the use is more frequent or the alarm cycle is set for more than 1 minute the battery life may be reduced.
Using optional power supply with adapter 12V/1A will extend the battery life.

Functional Specifications

- Suitable for outdoor mounting
- Bi-directional tamper switch for self-protection of the box
- Separate alarm notifications for intrusion and fire
- Squawk functionality
- Reset button for restoring the factory settings
- Internal metal cover for increased protection
- Plastic cover for protection of the electronic components
- Additional external power supply with adapter
- Chasing LEDs optional switching

Contact Information



BRAVO SR300 Li Wireless Outdoor Siren

EN 50131
GRADE 2 Class IV

● Packing Information

- **Single packing box** - 1 unit BRAVO SR300 Li, dimensions 332 x 238 x 67mm
- **Master packing box** - 5 units BRAVO SR300 Li, dimensions 360 x 345 x 252mm

● Compatible Product Range

- **BRAVO EXT** - Wireless panel with external power supply
- **BRAVO INTR** - Wireless panel with built-in power supply
- **ECLIPSE WL** - Wireless expander module for ECLIPSE control panels

● Contact Information